

Z8 Laser Cutting Machine Part



Mark & model: Output power of Z8 is between 150w and 180w. High-power laser tube, with long service time, is capable to cut thin metal plate.

Origin: Asia and Pacific Area China

Quality standard: International

H.S. Classification: Machinery & Electronics Electr. Element 8541

Semiconductor devices; light-emitting diodes etc.; parts thereof

Z8 Operation Instruction

1. Installation Requirement

Make sure to follow the operation instruction of model Z8 as shown in the illustration. The dedicated power DY20 should be equipped. The positive pole of laser tube is in high voltage (the ignition voltage is 30kv). It may cause the following consequence when it is failed to follow the instruction: The cutting speed will be slowed because of the deformation of beam output model; Arcing; the inner tube will be punctured by electricity and may cause water leakage.

2. Operation conditions

Water cooling: using purified water; 3 to 5 liter/minute; water temperature: 10°C-40°C. The operating environment: temperature 2-40°C; humidity 10-60%. The working current: test current is 32mA. Maximum working current is 32mA. The running current must be kept below 30mA. The life span can reach 10,000 hours if the current is kept below 28mA. The ammeter must be connected to the negative electrode of laser tube. When it is working under overhigh current for long term, the negative pole will appear purple and the

life span will be shortened rapidly.To protect dust from going into the insulation sheath, please wrap it with plastic film.

3.Working Performance

Cutting function.Engraving function: Auxiliary Engraving. When the working current is 4mA and the tube is in the state of preionization, the laser can be used for high-frequency impulse engraving.

4.Key Notes

Do not clean the exterior surface of the output widow mirror with tools such as tampon; otherwise the output power will be seriously affected. The followings are the designated methods to clean up pollution in the exterior surface of window mirror.

- 1) When the mirror is polluted, do not turn on the laser.
- 2) Blow the mirror surface sideways with an air blower.
- 3) Spray the pure alcohol on the mirror surface with sprayer.
- 4) Turn on the laser after the alcohol gets fully volatilized.
- 5) If the methods above don't work effectively, it is necessary to go after the professional workers to use tampon with alcohol to clean the mirror surface from middle to edge. The best solution is to prevent the window from being polluted.

Attention: it is forbidden to clean the mirror with acetone.The screw in the front and back ends of the laser tube is not allowed to be moved, otherwise the out power will be declined, even the laser will be scrapped.Put the acryl 300mm far away from output mirror,when testing the laser spot.

5.Safety

The laser beam is invisible light. Please wear protective glasses when debugging the laser. The positive pole is in high voltage. Pay attention to the security marks.

6.Storage and Transportation Requirement

Pour out cooling fluid in the event of storage and transportation, and cover the output terminal with a dust-proof plastic bag. The storage environment is 2-40℃, and the requested humidity is 10-60%. Pack the laser as in the original way. Important notes: it is requested to cement the sponge together with laser

tube to prevent the tube vertically sliding during transportation. The sponge in the side of output mirror must be 70 mm beyond it, and the sponge in the side of reflecting mirror must be 50 mm wider.

7. Tubes operated in wrong way are not guaranteed by Manufacturer. Idealphotonics

Cardboard Carton Package Size

DESCRIPTION	N.W.	G.W.	PACKAGE/UNIT	C.W.	CBM
Laser Tube Z2 (90W)	3.5KG	5KG	1360*250*260 mm	18KG	0.088
Laser Tube Z4 (100W)	4KG	7KG	1550*340*350 mm	36.9 KG	0.18 4
Laser Tube Z6 (130W)	5KG	8KG	1800*340*350 mm	43KG	0.21 4
Laser Tube Z8 (150W)	6KG	11KG	2010*380*400 mm	62.4 KG	0.30 4

Laser Tube basic parameter

Model	Rated power	Max power	length mm	Φ mm	Catalyze	Life span (h)	Warranty
Z2	90W	100w	1200	80	Yes	10,000	10Months
Z4	100W	130w	1400	80	Yes	10,000	10 Months
Z6	130W	160w	1650	80	Yes	10,000	10 Months
Z8	150W	180w	1850	90	Yes	10,000	10 Months