

Super Long-Distance Collimating Lens 1550nm (2KM Focal Length 250mm SMA905)



● Product Description

The optical fiber output is collimated and reshaped into a large spot, suitable for high-power, long-distance transmission, and pulsed output lasers. Within the operating range, the light exhibits excellent collimation, with a uniform energy distribution and sharp, clear edges. The design adopts a multi-lens series with air gaps, compatible with single-mode, multi-mode, and large-core optical fibers, enabling functions such as remote sensing, illumination, and interference.

● Part Number

NIR-CLM-W1550-80-2-62.5/125-SMA905

● Product features

Standard fiber optic input with FC or SMA connectors , Collimated space beam output , Suitable for wavelengths in the range of 405 nm to 1.55 μm , Collimation distance suitable for ≥ 2 km , Beam energy concentration , Multi-lens design with dual-sided antireflection coating on lenses to improve transmission efficiency

Parameters

525nm Ultra-long Distance Collimating Lens						
Working Wavelength	Output Spot Diameter	Beam Divergence Angle	Effective Focal Length mm	Transmission Distance	Fiber Type	Connector
525 \pm 20nm	80	0.20mrad	250	2km	62.5/125	FC/APC
	100	0.15mrad	320	3km		FC/PC
	150	0.10mrad	400	5km		SMA905
905nm Ultra-long Distance Collimating Lens						
Working Wavelength	Output Spot Diameter	Beam Divergence Angle	Effective Focal Length mm	Transmission Distance	Fiber Type	Connector
905 \pm 20nm	80	0.20mrad	250	2km	62.5/125	FC/APC
	100	0.15mrad	320	3km		FC/PC
	150	0.10mrad	400	5km		SMA905
1550nm Ultra-long Distance Collimating Lens						
Working Wavelength	Output Spot Diameter	Beam Divergence Angle	Effective Focal Length mm	Transmission Distance	Fiber Type	Connector
1550 \pm 20nm	80	0.20mrad	250	2km	62.5/125	FC/APC
	100	0.15mrad	320	3km		FC/PC
	150	0.10mrad	400	5km		SMA905