

# 7InGaAs avalanche photodiode detector APD-400M-A



## ● Product Description

The avalanche unit detection module integrates a low-noise APD detector, low-noise broadband transimpedance amplifier, ultra-low noise isolated power supply, high-voltage power supply, and APD temperature compensation. The isolated power supply ensures that the output signal is not affected by external power supply interference. APD temperature compensation improves the stability of the detection module. The avalanche photodetector features high gain, high sensitivity, high bandwidth, and low noise.

## ● Part Number

APD-400M-A

## ● Product features

Low noise、High gain、Built-in high-voltage power supply、APD temperature compensation、Compact structure、Built-in low-noise isolated power supply

## ● Application area

Fiber sensing、Fiber optic communication、Laser ranging、Spectral measurement、Nanosecond-level optical pulse detection

## Parameters

### General parameters

| PN#                 | AP<br>D-1<br>00<br>M-<br>A | AP<br>D-2<br>00<br>M-<br>A | AP<br>D-3<br>00<br>M-<br>A | AP<br>D-4<br>00<br>M-<br>A | AP<br>D-5<br>00<br>M-<br>A | AP<br>D-6<br>00<br>M-<br>A | AP<br>D-8<br>00<br>M-<br>A | AP<br>D-1<br>G-A | AP<br>D-1.2<br>G-A | AP<br>D-1.5<br>G-A | AP<br>D-2<br>G-A | AP<br>D-2.5<br>G-A | AP<br>D-5G-<br>A | Unit             |
|---------------------|----------------------------|----------------------------|----------------------------|----------------------------|----------------------------|----------------------------|----------------------------|------------------|--------------------|--------------------|------------------|--------------------|------------------|------------------|
| Detector type       | InGaAs                     |                            |                            |                            |                            |                            |                            |                  |                    |                    |                  |                    |                  |                  |
| Wavelength          | 800~1700                   |                            |                            |                            |                            |                            |                            |                  |                    |                    |                  |                    |                  | nm               |
| Bandwidth           | 100<br>M                   | 200<br>M                   | 300<br>M                   | 400<br>M                   | 500<br>M                   | 600<br>M                   | 800<br>M                   | 1G               | 1.2<br>G           | 1.5<br>G           | 2G               | 2.5<br>G           | 5G               | Hz               |
| Responsivity        | 9                          | 9                          | 9                          | 9                          | 9                          | 9                          | 9                          | 9                | 9                  | 9                  | 9                | 9                  | 9                | V/W              |
| Transimpedance gain | 300<br>K                   | 300<br>K                   | 300<br>K                   | 100<br>K                   | 50K                        | 50K                        | 300<br>K                   | 300<br>K         | 300<br>K           | 200<br>K           | 150<br>K         | 150<br>K           | 30K              | V/W              |
| Output impedance    | 50                         | 50                         | 50                         | 50                         | 50                         | 50                         | 50                         | 50               | 50                 | 50                 | 50               | 50                 | 50               | Ω                |
| Saturation power    | 13                         | 13                         | 13                         | 39                         | 78                         | 78                         | 13                         | 13               | 13                 | 20                 | 26               | 26                 | 78               | uW               |
| NEP                 | 0.4<br>6                   | 0.4<br>6                   | 0.4<br>6                   | 0.4<br>6                   | 0.4<br>6                   | 0.4<br>6                   | 0.4<br>6                   | 0.4<br>6         | 0.4<br>6           | 0.4<br>6           | 0.4<br>6         | 0.4<br>6           | 0.4<br>6         | pW/<br>√<br>(Hz) |

| Output coupling method | DC/AC                                      | DC/AC     | DC/AC     | DC/AC     | DC        | DC        | AC        | AC        | AC        | AC        | AC        | AC        | AC        |    |
|------------------------|--------------------------------------------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|----|
| Supply voltage         | 5                                          | 5         | 5         | 5         | 5         | 5         | 12        | 12        | 12        | 12        | 12        | 12        | 12        | V  |
| Supply current         | 0.5 (max)                                  | 0.5 (max) | 0.5 (max) | 0.5 (max) | 0.5 (max) | 0.5 (max) | 0.5 (max) | 0.5 (max) | 0.5 (max) | 0.5 (max) | 0.5 (max) | 0.5 (max) | 0.5 (max) | A  |
| Optical input          | FC/APC (Free space optical input optional) |           |           |           |           |           |           |           |           |           |           |           | FC/APC    |    |
| RF output              | SMA                                        |           |           |           |           |           |           |           |           |           |           |           | SMA       |    |
| Dimensions             | 65*50*20                                   |           |           |           |           |           | 65*50*25  |           |           |           |           |           | 80*90*25  | mm |

## Test result

